

## SAFETY DATA SHEET

**Item Code: N0766**

<b>Section 1.</b>	<b>Identification of the material and the supplier</b>
-------------------	--

Item Code:	N0766
Product:	Lube-R-Coat Aerosol
Product Use:	Lubricant
New Zealand Supplier:	Realcold Ltd
Address:	9 Prescott Street Penrose, Auckland
Telephone:	09 526 5700
Fax Number:	09 526 5721
<b>Emergency Telephone:</b>	<b>09 526 5700</b> <b>0800 766 764 (National Poison Centre)</b>
Manufacturer:	The RectorSeal Corp, 2601 Spenwick Dr, Houston, USA
Date of MSDS Preparation:	14 march 2017 – ver 2

<b>Section 2.</b>	<b>Hazards Identification</b>
-------------------	-------------------------------

**The manufacturer has stated that this substance is hazardous according to the *HSNO (Minimum Degrees of Hazard) Regulations 2001***

**Pictograms**

HSNO Class: 2.1.2A (Flammable Aerosol)



Flammable

**Acute hazards**

Repeated inhalation may cause dizziness, nausea and CNS effects. May cause severe eye and skin irritation.

**Route of exposure, signs and symptoms**

<b>Inhalation:</b>	Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.
<b>Eye contact:</b>	Contact with eyes may cause severe irritation.
<b>Skin contact :</b>	Irritation and drying.
<b>Ingestion:</b>	May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

### Chronic hazards

Skin irritation, contact dermatitis, and defatting.

### Medical conditions aggravated by exposure

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

## Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Kerosene	Not available	8008-20-6
Base Stock Oil	Not available	64742-54-7

## Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Immediately flush eyes with gentle but large stream of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Call a physician immediately.
If on Skin	Remove contaminated clothing and wash skin with warm soapy water. Do not scrub. If swelling, redness, blistering or irritation occurs, get medical assistance
If Swallowed	If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

## Section 5. Fire Fighting Measures

<b>Hazard Type</b>	Flammable
<b>Hazards from decomposition products</b>	CO, CO, and fragmented hydrocarbons.
<b>Suitable Extinguishing media</b>	Foam, dry chemical, CO <sub>2</sub> , or water fog.
<b>Precautions for firefighters and special protective clothing</b>	Wear self-contained full face piece breathing apparatus and full body protective clothing. Evacuate area. Dike area as run-off may create additional environmental contamination.
<b>HAZCHEM CODE</b>	<b>2YE</b>

## Section 6. Accidental Release Measures

Use absorbent materials to prevent footing hazard and to contain. Ventilate area with forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

## Section 7. Handling and Storage

<b>Handling</b>	Shake well before using. Keep away from heat and open flames. . Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions.
<b>Storage</b>	Prolonged exposure to direct sunshine or storage above 49°C may cause can to burst. Do not puncture or incinerate can

## Section 8 Exposure Controls / Personal Protection

**Engineering Controls** Local exhaust acceptable

### Personal Protection

**Respiratory:** In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirator.

**Gloves:** Wear rubber gloves.

**Eyes:** Safety glasses (ANSI Z-87.1 or equivalent)

**Other:** Chemical resistant coveralls recommended.

Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area.

Launder contaminated clothing before reuse.

## Section 9 Physical and Chemical Properties

<b>Appearance</b>	Amber Liquid
<b>Odour</b>	Petroleum Odour
<b>Flash Point</b>	86°C
<b>Boiling Point</b>	160°C @ 760mm Hg
<b>Evaporation Rate</b>	>1
<b>Specific Gravity</b>	<1
<b>Solubility in Water</b>	Insoluble

## Section 10. Stability and Reactivity

<b>Stability of Substance</b>	Stable
<b>Conditions to Avoid</b>	Do not store in temperatures above 49°C
<b>Incompatible Materials</b>	Oxidizers, acids and bases.
<b>Hazardous Decomposition Products</b>	CO, CO, and fragmented hydrocarbons.

## Section 11 Toxicological Information

Kerosene  
Oral-Rat LD50:>5 g/kg

Base Stock Oil  
Oral-Rat LD50:>5 g/kg

### Acute hazards

Repeated inhalation may cause dizziness, nausea and CNS effects. May cause

Product Name: Lube-R-Coat Aerosol Item No: N0766  
Date of MSDS: 13 January 2012

Issued by: Realcold  
Tel: 64 9 526 5700

severe eye and skin irritation.

### Route of exposure, signs and symptoms

**Inhalation:** Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

**Eye contact:** Contact with eyes may cause severe irritation.

**Skin contact :** Irritation and drying.

**Ingestion:** May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

### Chronic hazards

Skin irritation, contact dermatitis, and defatting.

### Medical conditions aggravated by exposure

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

## Section 12. Ecotoxicological Information

Kerosene

Food Chain Concentration Potential: None  
WATERFOWL TOXICITY: N/A  
BOD: 53%  
AQUATIC TOXICITY: N/A

## Section 13. Disposal Considerations

Aerosol: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. Dispose of all liquid waste in accordance with all Local Regulations.

## Section 14 Transport Information

Classified as a Dangerous Good for transport

Road and Rail Transport (in NZ ; NZS 5433:2007)

UN No: 1950  
Class-primary 2.1  
Packing Group Not allocated  
Proper Shipping Name: AEROSOLS

Air Transport

UN No: 1950  
Class-primary 2.1  
Packing Group Not allocated  
Proper Shipping Name: AEROSOLS

Marine Transport

UN No: 1950  
Class-primary 2.1  
Packing Group Not allocated  
Proper Shipping Name: AEROSOLS

**Section 15 Regulatory Information**

Allocated to HSNO Group Standard "Lubricants (combustible) HSR002602

**Section 16 Other Information**

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.

**Disclaimer**

This document has been issued by Realcold Limited and serves as their Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to Realcold Limited or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While Realcold Limited have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Realcold Limited accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, Realcold Ltd, if further information is required.

Issue Date: 13 January 2012

Review Date: 13 January 2017