



**SPECIFICATION 规格说明**

MOTOR 电机型式	Shaded pole motor 罩极电动机
MOTOR TYPE 电机型号	YZF25-40
VOLTAGE 额定电压 (V)	230
FREQUENCY 频率 (Hz)	50
INPUT POWER 输入功率 (W)	90
CURRENT 电流 (A)	0.70
SPEED 负载转速 (r/min)	1300
FAN BLADES 负载风叶	Φ300 / 25° (MAX)
ROTATION 旋转方向	CCW (looking towards the shaft 从轴伸端视去逆时针方向)
AIRFLOW DIRECTION 风向	Sucking or Blowing 通过配不同扇叶实现吹吸风
MOTOR PROTECTION 电机保护方式	Terminal protection 热保护
INSULATION CLASS 绝缘等级	Class B B级绝缘
TEMPERATURE RISE 温升	95K max (with load) 负载运行温升不超过95K
PROTECTION CLASS 防护等级	IP 42
OPERATING TYPE 工作定额	S1 连续工作制
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
AMBIENT TEMPERATURE 适用环境温度	-25°C +50°C
BEARINGS 轴承型式	Sleeve bearings 含油轴承
ELECTRICAL CONNECTION 电源线	RV 3G 0.5mm <sup>2</sup> lead wire 960-1040mm free length 电源线长960-1040mm. 型号: RV-90 3G 0.5mm <sup>2</sup>
HI-POT TEST 耐压测试	1800V/1s I <sub>leakage</sub> ≤ 0.8mA 1800V/历时1秒, 泄漏电流 ≤ 0.8mA
APPROVALS 认证标记	CE
WEIGHT PER UNIT 单个电机净重	1.8kg
PACKAGING 包装	12PCS/CTN 12台/箱

电机标签: 50×11  
  
 YFDX25 25/90W  
 220-240V 50/60Hz  
 1300r/min KX/2023

内盘标签: 100×70  
  
 Fan Motor  
 YFDX25 25/90W  
 220-240V 50/60Hz  
 CL.B 1300r/min

纸箱正吸:



纸箱侧吸:

MODEL: YFDX25  
 QTY.: 12PCS  
 G.W.: 24kg  
 N.W.: 22kg  
 MEAS: 45cm×35.5cm×15cm

REV.	DESCRIPTION	APPROVED	DATE	SIGN	DATE	TITLE
				DRN BY	16/03/2023	YZF25-40-18/26
				CHD BY		
				ENG BY		PROJECTION
				APP BY		SCALE: A4
						SHEET: 1 of