



电机标签: 50×11
 CE UK
 YFDX10 10/36W
 220-240V 50/60Hz
 CL.B 1300r/min xx/2023

内盒标签: 100×70
 CE UK
 Fan Motor
 YFDX10 10/36W
 220-240V 50/60Hz
 CL.B 1300r/min
 freddox



纸箱侧唛:
 MODEL: YFDX10
 QTY.: 24PCS
 G.W.: 29Kg
 N.W.: 27Kg
 MEAS: 45cm×35.5cm×23cm
 CE UK

SPECIFICATION 规格说明

MOTOR 电机型式	Shaded pole motor 罩极电动机
MOTOR TYPE 电机型号	YZF10-20
VOLTAGE 额定电压 (V)	230
FREQUENCY 频率 (Hz)	50
INPUT POWER 输入功率 (W)	36
CURRENT 电流 (A)	0.25
SPEED 负载转速 (r/min)	1300
FAN BLADES 负载风叶	Φ230 / 28° (MAX)
ROTATION 旋转方向	CCW (looking towards the shaft 从轴伸端视去逆时针方向)
AIRFLOW DIRECTION 风向	Sucking or Blowing 通过配不同扇叶实现吹吸风
MOTOR PROTECTION 电机保护方式	Impedance protection 阻抗保护
INSULATION CLASS 绝缘等级	Class B B级绝缘
TEMPERATURE RISE 温升	95K max (with load) 负载运行温升不超过95K
PROTECTION CLASS 防护等级	IP 42
OPERATING TYPE 工作定额	S1 连续工作制
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
AMBIENT TEMPERATURE 适用环境温度	-25°C +50°C
BEARINGS 轴承型式	Sleeve bearings 含油轴承
ELECTRICAL CONNECTION 电源线	RV 3G 0.5mm ² lead wire 1000-1050mm free length 电源线长1000-1050mm, 型号: RV-90 3G 0.5mm ²
HI-POT TEST 耐压测试	1800V/1s I _{leakage} ≤ 0.8mA 1800V/历时1秒, 泄漏电流 ≤ 0.8mA
APPROVALS 认证标记	CE
WEIGHT PER UNIT 单个电机净重	1.1kg
PACKING 包装	24PCS/CTN 24台/箱

纸箱正唛:

纸箱侧唛:

REV.	DESCRIPTION	APPROVED	DATE	SIGN	DATE	TITLE
				DRN.BY	16/03/2023	YZF10-20-18/26
				CHD.BY		
				ENG.BY		
				APP.BY		
						PROJECTION
						A4
						SCALE:
						SHEET: 1 of